

SUBWOOFERS

CSUB Powered Subwoofers

CSUB compact active subwoofer with 100 V and line level inputs

CSUB

CSUB is a compact active subwoofer for mounting on flat surfaces. It has 10" driver, 200 W class-D amplifier, DSP based EQ correction and built-in audio limiter. Subwoofer can pick up audio from 100 V lines and has a specially designed DSP setting to recover low-frequencies, lost in constant voltages audio lines. Amplifier has a switchable automatic stand-by function for energy-saving benefits. CSUB is made from laminated MDF and is available in Black or White colours. Wall mounting brackets are included.



Technical Specifications	CSUB
Rated output power	200 W
Max power consumption	300 W
Stand by power consumption	3 W
Power supply	~ 220-230 V, 50 Hz
Driver dimensions	10" (254 mm)
Sensitivity	84 dB (1 W / 1 m)
Max. SPL	107 dB
Frequency Response	35 Hz - 150 Hz
Crossover point	40 Hz - 120 Hz
Inputs	1 x Stereo RCA, 1 x Mono hi-level input
RCA input sensitivity	-14dBu
RCA input impedance	10 kΩ
Cooling	Passive cooling
Material	Laminated MDF
Colour	Black (RAL 9017), White (RAL 9016)
Dimensions (H x W x D)	44 x 430 x 245 mm
Weight	10.6 kg

